

## CONCRETE POOL - ABS INLETS



### Return inlet "Multiflow" to glue



To glue onto  $\varnothing$  63 mm, outside 6 bar pipe and inside  $\varnothing$  50 mm. Made in white ABS. Can be installed with wall conduits: 15661-15660.

Code	S tandard Packaging	S tandard Weight kg	S tandard Volume m <sup>3</sup>
00298	24	4.24	0.020



### Return inlet "ultiflow" to glue



To glue into  $\varnothing$  50mm 10 bar pipe. Made in white ABS.

Code	S tandard Packaging	S tandard Weight kg	S tandard Volume m <sup>3</sup>
24413	40	4.0	0.020

Optional colour



### Concrete floor inlet



Return / Suction. Adjustable flow. Made in white ABS, screw in S.S. Max. flow rate: 12 m<sup>3</sup>/h complies with EN 13451-1 Standard.

Code	S tandard Packaging	S tandard Weight kg	S tandard Volume m <sup>3</sup>
00303	24	5.0	0.020
20140	20	4.4	0.021

2" male thread, inner  $\varnothing$  50 mm to glue

To glue onto  $\varnothing$  63 mm PN 6, inner  $\varnothing$  50 mm



### Return inlet "Multiflow" (threaded)



2" male thread, inner  $\varnothing$  50 mm for glueing. Made in white ABS. Can be installed with wall conduits: 15658- 15659.

Code	S tandard Packaging	S tandard Weight kg	S tandard Volume m <sup>3</sup>
00295	24	4.35	0.020



### Return inlet "Multiflow" to glue

To glue into  $\varnothing$  50mm 10 bar pipe. Made in white ABS

Code	S tandard Packaging	S tandard Weight kg	S tandard Volume m <sup>3</sup>
00292	40	4.0	0.020