

Commercial bobbin wound filter

STANDARD FEATURES

- Bobbin wound filters manufactured with polyester resin and fiberglass.
- Color filter Ral 5005.
- Arm collectors of 1".
- Filtration bed depth 1m.
- Sand drain 2 ½" up to diameter 2000, sand drain 3" in diameter 2350.
- Gauge panel optional.
- Air and water drain of ¾"
- Maximum temperature of 40°.
- Maximum pressure 2,5 or 4 Bar.

Code filter 2,5 Bar	32001	32002	32003	32004	32005	32006	32007
Code filter 4 Bar							
Ø (mm)	1050	1200	1400	1600	1800	2000	2350
Connections (mm)	75	90	110	110	125	140	160
Filtrating velocity (m3/h/m2)	40	40	40	40	40	40	40
Filtration Area (m2)	0,86	1,13	1,54	2,01	2,54	3,14	4,34
Flow (m ³ /h)	34	45	61	80	101	125	175
Sand (0,4-0,8mm)	950	1375	1650	2150	2800	3800	5275
Gravel (1-2mm) (kg)	300	300	450	675	750	1050	1800
Net weight (kg)	110	125	185	215	250	330	530
H (mm)	1640	1780	1755	1835	1875	2040	2520
M (mm)	645	640	610	515	465	510	600
N (mm)	540	570	585	680	720	790	965
P (mm)	755	940	1085	1230	1370	1550	1859
HF (mm)	1000	1000	1000	1000	1000	1000	1000
Packaging (m)	1,15x1,15x1,85	1,31x1,31x1,97	1,48x1,48x1,89	1,72x1,72x2	1,88x1,88x2,01	2,1x2,1x2,3	2,66x2,66x2,67

